

Application

Designed for stacking very large and heavy individual panels into dedicated areas on industrial and commercial applications where folding panels would not be suitable.

Each panel is supported by two hangers which can negotiate 45°, 135° and swept 90° switches.

Floor channel is not necessary since the panels may be secured in position by stops, flush bolts or locks.

To cover any width of opening, any number of panels can be used.

Stainless steel hangers make Stackadoor 200 ideal for installations close to the waterfront, in areas with a high corrosive atmosphere or to comply with food or health regulations.

Panel Specification

Track System:	Stackadoor 200
For Individual Panels:	
Max Panel Height	3000mm
Max Panel Weight	200kg
Min Panel Thickness	35mm for timber

Frameless toughened glass panels require a top rail for securing the M10 hanger bolts plus a bottom rail for securing the locks or bolts.

Timber panels can be flush, panelled or glazed. Suitable also for metal framed panels.

Panels should be constructed to provide secure fitting for the hangers.

Hardware Specification

Track:	500
Material	Aluminium, Clear Anodised
Standard Lengths	6000mm

Stacking bays are made to order for each application.

Fasten track at 500mm maximum centres with M10 stainless steel bolts, reducing to 250mm centres at stacking area and switches. Fasten at 25mm from track ends and joints.

Track Joining Plate:	500J180
-----------------------------	---------

Four required at each butt joint in the track.

Pivot Set:	500P10SS
-------------------	----------

Top and bottom pivots for single access panel.

Hangers (2 per panel):

Hanger and bolt	500HWS10
-----------------	----------

Hangers are fitted with stainless steel ball race wheels and all other components are in stainless steel. Vertical adjustment is simple and positive.

Hanger with flat plate	500HWS/61SK
Hanger with corner bracket	500HWS/21SK

Door Stop	500DS
------------------	-------

Accessories:

Flush Pulls	401
Flush Bolts	456



