

Application

For timber sliding panels on interior and exterior applications.

Designed for straight sliding partitions or fully glazed patio doors. Also suitable for flush panelled construction.

The bottom roller design is suited to applications where the supporting structure or lintel is insufficient for the weight of the panel or where headroom is limited.

To cover the width of opening, any number of panels can be used on single or multiple lines of rail. Panels can slide to one or both sides.

Where fitted externally, a canopy is recommended to protect the top guide channel, brackets and top guide rollers.

Panel Specification

Rail System:

For Individual Panels:
Max Panel Height
Max Panel Weight
Min Panel Thickness

Timberoll 170

2600mm
170kg
40mm

Panels must be constructed with bottom rails of at least 150mm depth to accommodate the concealed, mortised, bottom rollers. Panel weight is carried on the floor permitting the use of a light overhead structure.

Hardware Specification

Top Guide Channel:

Medium Duty
Material 94PPA Aluminium Support & Polypropylene
Finish Mill or Clear Anodised
Standard Lengths 2000mm, 3000mm, 4000mm and 6000mm.

Heavy Duty
Material 900 Aluminium with safety lip
Finish Clear Anodised
Standard Lengths 2000mm, 3000mm, 4000mm and 6000mm.

Top Guide Brackets:

For single line - face fitted 1SS/250 Stainless Steel
For double line - face fitted 5SS/250 Stainless Steel

Constructed from cast 316 Stainless Steel, fit at 400mm maximum centres.

Top Guide Rollers (2 per panel):

Top Plate Fitting 106RB/94
Corner Fitting 113RB/94

Cast 316 Marine grade stainless with precision stainless steel bearings

Top Plate Fitting 61SS/900 (for 900 Top Guide Channel)
Cast 316 Marine grade stainless plate with double nylon rollers with lateral adjustment to prevent rattle.

Bottom Roller (2 per panel):


Bottom roller 913SBA
Stainless steel body, wheel and ball race

Bottom Rail:

Brass 913B Rail
918 Rail with edge guides
Standard lengths 2000mm, 3000mm, 4000mm and 6000mm.
These rails are drilled and countersunk for screwing to timber floor.

Accessories:

Door Collector - multiple panels 924-DC
Flush Bolt 456
Flush Pull 401
Frame Seal AQ21



No. 900A
GUIDE CHANNEL




No. 94PPA
CHANNEL



No. 913B
BOTTOM RAIL




No. 924-48BZ
INTERLOCKER




No. 61SS/900
TOP GUIDE ROLLER




No. 113RB/94
GUIDE ROLLER




No. 913SBA
BOTTOM ROLLER



No. 106RB/94
GUIDE ROLLER



No. 924-DC
DOOR COLLECTOR



No. 401
FLUSH PULL

